File No.	182JH22217	SHEET	1/1

△1 SPECIFICATION
Current:3A
Operation Temperature:−55°C~+105°C
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
△3 Withstanding Voltage:1000V AC/Minute
Housing:PA6T(UL94V−0),Black
△2 Contact:Brass,Gold Flash Over Nickel
No. Of Contacts:02~40 Contacts
RoHS Compliant



Recommended P.C.B. Layout



△1△3



△1△2△3



△1△2△3

△3	A3	Modify Data	HZF	08/22/2019
△2	A2	Modify Data	HZF	04/03/2014
△1	A1	Modify Data	HZF	11/01/2010
△0	A0	NEW RELEASE	SHIN	10/17/2006
NO.	REV.	REVISIONS	CHK	DATE

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △2	00810		
APPROVED BY	MEI		
CHECKED BY	HZF		
DRAWING BY	CYP		
SCALE	NONE	REV.	A3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
△3 .X ±0.38
.XX ±0.25
.XXX ±0.05
UNIT mm