




△ SPECIFICATION
 Current Rating:3A AC/DC
 Voltage Rating:250V AC/DC
 Withstand Voltage:800V AC/Minute
 Insulation Resistance:1000 Megaohms Min.
 Temperature Range:-25°C~+85°C
 Material:PA66(UL94V-2),Black
 RoHS Compliant



Pin	A	B
4	2.00	6.00
6	4.00	8.00
8	6.00	10.00
10	8.00	12.00
12	10.00	14.00
14	12.00	16.00
16	14.00	18.00
18	16.00	20.00
20	18.00	22.00
22	20.00	24.00
24	22.00	26.00
26	24.00	28.00
28	26.00	30.00
30	28.00	32.00
32	30.00	34.00
34	32.00	36.00

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. **01344**
 APPROVED BY EMILY
 CHECKED BY HZF
 DRAWING BY CYP
 SCALE NONE REV. A2

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X; ±0.5
 XX; ±0.25
 .XXX ±0.08
 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△2	A2	Modify Data	HZF	05/09/2015
△1	A1	Modify Data	HZF	09/23/2010
△0	A0	NEW RELEASE		