



△△ SPECIFICATIONS
 Current Rating:1A AC/DC
 Voltage Rating:250V AC/DC
 Withstand Voltage:500V AC/Minute
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Temperature Range:-40°C~+105°C
 Insulator:PBT+G.F.(UL94V-0),Black
 Contact:Brass,Selective Gold Plated Over Nickel
 RoHS Compliant

Pin	A	B
08	7.62	15.42
10	10.16	17.96
14	15.24	23.04
16	17.78	25.58
18	20.32	28.12
20	22.86	30.66
24	27.94	35.74
28	33.02	40.82
32	38.10	45.90
40	48.26	56.06

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ .X ±0.2 △.XX ±0.10 ANG.
03770		MEI		
		HZF		
		DRAWING BY		UNIT mm
		CYP		
SCALE	NONE	REV.	B4	NO. REV.

△	B4	Modify Data	HZF	01/17/2015
△	B3	Modify Data	HZF	11/01/2013
△	B2	Modify Data	HZF	12/12/2012
△	B1	Modify Data	HZF	07/15/2008
△	B0	NEW RELEASE	BECKY	06/14/2006
NO. REV.	REVISIONS		CHK	DATE