



△△ SPECIFICATIONS
 Current Rating:1A AC/DC
 Voltage Rating:250V AC/DC
 Withstand Voltage:500V AC/Minute
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Temperature Range:-40°C~+105°C
 Insulator:PBT+G.F.(UL94V-0),Black
 Contact:Brass,Selective Gold Plated Over Nickel
 RoHS Compliant

| Pin | A | B |
|-----|-------|-------|
| 08 | 7.62 | 15.42 |
| 10 | 10.16 | 17.96 |
| 14 | 15.24 | 23.04 |
| 16 | 17.78 | 25.58 |
| 18 | 20.32 | 28.12 |
| 20 | 22.86 | 30.66 |
| 24 | 27.94 | 35.74 |
| 28 | 33.02 | 40.82 |
| 32 | 38.10 | 45.90 |
| 40 | 48.26 | 56.06 |

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

| | | | | |
|-------------|------|-------------|-----|--|
| DRAWING No. | | APPROVED BY | | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ .X ±0.2 △.XX ±0.10 ANG. |
| 03777 | | MEI | | |
| | | CHECKED BY | HZF | |
| SCALE | | DRAWING BY | CYP | |
| NONE | REV. | B4 | | UNIT mm |

| | | | | |
|-----|------|-------------|-------|------------|
| △ | B4 | Modify Data | HZF | 01/17/2015 |
| △ | B3 | Modify Data | HZF | 11/01/2013 |
| △ | B2 | Modify Data | HZF | 12/12/2012 |
| △ | B1 | Modify Data | HZF | 07/15/2008 |
| △ | B0 | NEW RELEASE | BECKY | 06/14/2006 |
| NO. | REV. | REVISIONS | CHK | DATE |