



**△ SPECIFICATION**  
 Current Rating: 3 Amp  
 Withstand Voltage: 1000V AC  
 Contact Resistance: 20 Milliohms Max.  
 Insulation Resistance: 1000 Megaohms Min.  
 Operation Temperature: -40°C ~ +105°C  
 Insulator: PBT (UL94V-0), Black  
 Contact: Brass, Gold Flash Over Nickel  
 Only 60P ~ 64P With Slot "A"  
 Less Than 18 Pin Without Slot "B"  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY	
03796		MEI	
		CHECKED BY	HZF
		DRAWING BY	CYP
SCALE	NONE	REV.	A3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE					
△	X. ±0.25	X.*	±2°		
△	.X ±0.20	.X*	±1.5°		
△	.XX ±0.15	.XX*	±1°		
△	.XXX ±0.10	.XXX*	±0.5°		
UNIT	mm				
NO.	REV.	REVISIONS		CHK	DATE
△3	A3	Modify Data		HZF	05/29/2015
△2	A2	Modify Data		HZF	04/22/2015
△1	A1	Modify Data		HZF	03/06/2014
△0	A0	NEW RELEASE		HZF	05/16/2012