

△ SPECIFICATION
 Current Rating:1 Amp
 Withstanding Voltage:500V AC For 1 Minute
 Insulation Resistance:3000 Megaohms Min.
 Contact Resistance:30 Milliohms Max.
 Operation Temperature:-40°C~+105°C
 Insulator:PBT+G.F.(UL94V-0),Black
 Contact:Brass,Selective Gold Flash Over Nickel
 RoHS Compliant

△ Pin	A	B	C	Pin	A	B	C
10	22.36	15.50	10.16	44	65.54	58.68	53.34
14	27.44	20.58	15.24	50	73.16	66.30	60.96
16	29.98	23.12	17.78	56	80.78	73.92	68.58
20	35.06	28.20	22.86	60	85.86	79.00	73.66
26	42.68	35.82	30.48	62	88.40	81.54	76.20
34	52.84	45.98	40.64	64	90.94	84.08	78.74
40	60.46	53.60	48.26				

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.


DRAWING No.
 04561

APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 ANG.

SCALE NONE

REV. B3



NO.	REV.	REVISIONS	CHK	DATE
	B3	Modify Data	HZF	04/17/2015
	B2	Modify Data	HZF	04/17/2014
	B1	Modify Data	HZF	07/31/2011
	B0	NEW RELEASE	BECKY	09/01/2005