



File No. 112 SHEET 1 / 1










MATERIAL
Insulator: LCP,UL 94V-0 Rated
Contact: Phosphor Bronze,t=0.25mm
Shell: Phosphor Bronze,t=0.40mm

SPECIFICATIONS
Current Rating: 1A Max.
Dielectric Withstanding Voltage: 500V(AC) For 1 Minute
Contact Resistance: 30 Milliohms Max.
Insulation Resistance: 1000 Megohms Min. At DC 500V
Total Mating Force: 4.0 Kgf Max.
Total Unmating Force: 1.0 Kgf Min.
Temperature Range: -55℃~+105℃

FINISHES
Contact: Gold Plated 15u"
Shell: Nickel Plated



P.C.B. Layout

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No. 09558	APPROVED BY MEI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.3 .XX ±0.20 ANG. ±1°			
	CHECKED BY BECKY				
	DRAWING BY HZF				
SCALE NONE	REV. B0	UNIT mm	0 B0	NEW RELEASE	BECKY 05/11/2005
			NO. REV.	REVISIONS	CHK DATE