



Recommended P.C.B. Layout

SPECIFICATION
 Current Rating:1A
 Withstanding Voltage:500V AC At Sea Level
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Mating Force:3.5 Kg Max.
 Unmating Force:1 Kg Min.
 Operation Temperature:-55°C~+85°C
 RoHS Compliant

③	Housing	PBT	Black	1
②	Terminal	C5191H	Gold Plated 30u" On Contact Area, Tin Plated On Solder Tails, Over Nickel	4
①	Shell	Brass	Nickel Plated	1
No.	Description	Material	Remark	Q'ty

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ X° ±2.0° .X ±0.2 .X° ±1.0° .XX ±0.1 .XX° ±0.5°
11083		MEI		
		CHECKED BY HZF		
		DRAWING BY CYP		UNIT mm
SCALE	NONE	REV.	A1	

△ A1	Modify Data	HZF	12/15/2017
△ A0	NEW RELEASE	HZF	03/29/2015
NO.	REV.	REVISIONS	CHK DATE