


△ SPECIFICATION
 Current Rating: 2 Amp/Way Max.
 Voltage Rating: 150V AC
 Withstanding Voltage: 2000V AC (1 Minute)
 Test Time = 60s/PCS
 Contact Resistance: 20 Milliohms Max.
 Wire Range: 20~26 AWG
 Operation Temperature: -40°C ~ +105°C
 Test Temperature: 250°C 5 Seconds Max.
 Wire Guard: Stainless Steel
 Surface Of Solder Tails: Copper Alloy, Tin Plated
△ Insulator Body (Housing): Polyamide+G.F. (UL94V-0), Green
 RoHS Compliant
 * 02~20P Available



4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1°
11356		EMILY		
		CHECKED BY HZF		
		DRAWING BY HAO		
SCALE	NONE	REV.	A2	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△2	A2	Modify Data	HZF	08/18/2020
△1	A1	Modify Data	HZF	05/12/2015
△0	A0	NEW RELEASE	HZF	05/23/2009