



Recommended P.C.B. Layout (Top View)
(PCB Board Tolerance ±0.05)

△△ SPECIFICATION

Current Rating: 1.5 A
 Operation Voltage: 100V AC Max.
 Dielectric Withstand Voltage: 500V AC
 Contact Resistance: 30 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Temperature Range: -25°C ~ +85°C
 Insulator: LCP+30%G.F.(UL94V-0), Black
 Contact: Brass
 Gold Flash On Contact Area, Tin Plated On Solder Tails, Over Nickel
 Boardlock: Brass, Tin Plated On Solder Tails, Nickel Plated Over All
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △.X ±0.25 X.* ±2° .X ±0.20 .X* ±1.5° .XX ±0.15 .XX* ±1° .XXX ±0.10 .XXX* ±0.5°
14877		MEI		
		CHECKED BY	HZF	
		DRAWING BY	CYP	
SCALE	NONE	REV.	A2	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△A2		Modify Data	HZF	10/28/2017
△A1		Modify Data	HZF	10/15/2013
△A0		NEW RELEASE	HZF	02/09/2011