



**SPECIFICATION**

**1. Material & Finish**  
 Insulator: LCP (UL94V-0), Black  
 Contact: Brass, Tin Plated  
 Solder Tabs: Brass, Tin Plated Over Nickel

**2. Electrical Characteristics**  
 Current Rating: 5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Contact Resistance: 20 Milliohms Max.  
 Insulation Resistance: 1000 Megaohms Min.  
 Δ Withstand Voltage: 1500V AC/Minute

**3. Environmental Characteristics**  
 Temperature Range: -40°C ~ +105°C

**4. RoHS Compliant**

Pin	A	B	C
2	--	6.65	4.30
4	3.00	9.65	7.30
6	6.00	12.65	10.30
8	9.00	15.65	13.30
10	12.00	18.65	16.30
12	15.00	21.65	19.30
14	18.00	24.65	22.30
16	21.00	27.65	25.30
18	24.00	30.65	28.30
20	27.00	33.65	31.30
22	30.00	36.65	34.30
24	33.00	39.65	37.30

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No. **18080**

APPROVED BY Jason Wu  
 CHECKED BY Leo Han  
 DRAWING BY Michelle Lee

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE  
 X. ±0.30  
 .X ±0.25  
 .XX ±0.20  
 .XXX ±0.05  
 ANG. ±1°

SCALE NONE REV. B1 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△	B1	Modify Data	HZF	07/21/2025
△	B0	Modify Data	HZF	02/20/2023
△	B0	NEW RELEASE	HZF	02/20/2023