



**△ SPECIFICATION**  
 Current Rating: 1 Amp  
 Dielectric Withstanding Voltage: AC 1000V For 1 Minute  
 Insulation Resistance: 1000 Megaohms Min. At DC 500V  
 Contact Resistance: 30 Milliohms Max. At DC 100mA  
**△ Operation Temperature:**  $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$   
 Housing: LCP, Nature  
 Contact: Brass,  
 Gold Plated 10u" On Contact Area  
 Tin Plated On Solder Tails, Over Nickel  
 RoHS Compliant

Pin	A	B	C
24	11.95	10.0	0.0
48	23.95	22.0	12.0
72	35.95	34.0	24.0
96	47.95	46.0	36.0
120	59.95	58.0	48.0
144	71.95	70.0	60.0
168	83.95	82.0	72.0
192	95.95	94.0	84.0

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No. <b>18215</b>		APPROVED BY EMILY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. $\pm 0.5$ .X $\pm 0.25$ .XX $\pm 0.15$
		CHECKED BY HZF		
		DRAWING BY YBL		
SCALE	NONE	REV.	A2	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A2		Modify Data	HZF	02/16/2022
△ A1		Modify Data	HZF	12/20/2013
△ A0		NEW RELEASE	HZF	01/02/2009