



△△ SPECIFICATION
 Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec./1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature=250°C±10°C/
 5 Seconds Max.
 Wire Range:12~26 AWG
 Torque:5.0 Kgf.cm/M3
 Insulator Body(Housing):Polyamide(UL94V-0),Green
 Contact(Metal Housing):Copper Alloy,Nickel Plated
 Wire Guard:Copper Alloy,Tin Plated
 Screw:Steel,Galvanized With Cr3+ Plated
 RoHS Compliant

4U CON 元化興業股份有限公司
 4U CON TECHNOLOGY INC.

| | | | | | | | | |
|--------------------------|------|--------------------|----|--|---------|-------------|-----|------------|
| DRAWING No. 19893 | | APPROVED BY MEI | | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1° | △ A4 | Modify Data | HZF | 08/07/2014 |
| | | CHECKED BY HZF | | | △ A3 | Modify Data | HZF | 02/12/2014 |
| | | DRAWING BY YBL | | | △ A2 | Modify Data | HZF | 12/16/2011 |
| SCALE | NONE | REV. | A4 | UNIT mm | △ A1 | Modify Data | HZF | 06/29/2010 |
| | | | | | △ A0 | NEW RELEASE | HZF | 04/10/2009 |
| | | | | | NO.REV. | REVISIONS | CHK | DATE |