




Recommended P.C.B. Layout  
Tolerance: ±0.05 (Top View)

**SPECIFICATION**  
 Current Rating: 3 Amp  
 Withstand Voltage: 1000V AC  
 Contact Resistance: 20 Milliohms Max.  
 Insulation Resistance: 1000 Megaohms Min.  
 Operation Temperature: -40°C ~ +105°C  
 Insulator: PBT(UL94V-0), Black  
 Contact: Brass, Gold Flash Over Nickel  
 RoHS Compliant



**4UCON** 元化興業股份有限公司  
4UCON TECHNOLOGY INC.

DRAWING No. $\Delta$		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	$\Delta$ A4	Modify Data	HZF	01/10/2023
20256		EMILY			$\Delta$ A3	Modify Data	HZF	04/17/2015
		CHECKED BY			$\Delta$ A2	Modify Data	HZF	11/20/2013
SCALE		NONE		$\Delta$ A1	Modify Data	HZF	09/03/2013	
		REV.		A4	$\Delta$ A0	NEW RELEASE	HZF	12/14/2010
				UNIT	NO. REV.		REVISIONS	CHK
				mm				DATE

DRAWING BY		HAO		UNIT		NO. REV.		REVISIONS	CHK	DATE
				mm						