



SPECIFICATION

1.General Characteristics
 Micro SIM Connector Push Push 06 Pin SMT 90°
 Standoff=0mm Noraml H=1.35mm Tape & Reel
 1000 PCS/Reel

2.Material&Finish
 Housing:LCP(UL94V-0)
 Contact:C5210,Gold Flash On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
 Shell:Stainless Steel,Gold Flash On Solder
 Tails,Over Nickel

3.Electrical Characteristics
 Current Rating:0.5 Amp Max.
 Voltage Rating:50V
 Contact Resistance:100 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 At 250V DC
 Dielectric Withstanding:500V AC

4.Mechanical Characteristics
 Durability:5000 Cycles

5.Environmental Characteristics
 Operation Temperature:-20°C~+60°C
 Storage Temperature:-40°C~+70°C
 Ambient Humidity Range:95% R.H. Max.
 Temperature:260±5°C

6.RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±1.00 X ±0.5 .XX ±0.25 .XXX ±0.15 ANG. ±2°					
21051		MEI			△ A2	Modify Data	HZF	03/22/2018	
		HZF			△ A1	Modify Data	HZF	07/25/2017	
		CYP		△ A0	NEW RELEASE	HZF	09/30/2016		
SCALE	NONE	REV.	A2	UNIT	mm	NO.REV.	REVISIONS	CHK	DATE