
| File No. | 626HF22233 | SHEET | 1/1 |
|---|---|---|---|

## SPECIFICATION

Voltage Rating:DC 300V AC 300V
Contact Resistance:2 Ohms
Insulation Resistance:20 Megaohms
Test Time 0.6 Sec.
Short/Open Circuit At Moment:4/Sec.(Being Flexed Test)
RoHS Compliant




| Pin Assignment | | |
|---|---|---|
| P1 | Color | P2 |
| 1 | Red | 1 |
| 2 | Orange | 2 |
| 3 | Black | 3 |

| Item | Name | Specification | Q'ty |
|---|---|---|---|
| ① | Wire | UL1007 26 AWG | 3 PCS |
| ② | Housing | PH 2.54mm MK Housing,3P | 2 PCS |
| ③ | Terminal | PH2.54mm MK Matching Terminal | 6 PCS |

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

| DRAWING No. | APPROVED BY | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE |
|---|---|---|
| 21062 | MEI | .X ±0.38 |
| | CHECKED BY HZF | .XX ±0.25 |
| | DRAWING BY CYP | ANG. |
| SCALE NONE | REV. A0 | UNIT mm |

| NO. | REV. | REVISIONS | CHK | DATE |
|---|---|---|---|---|
| ⓪ | A0 | NEW RELEASE | HZF | 06/22/2017 |