



Recommended P.C.B. Layout

SPECIFICATION

Withstanding Voltage:250V RMS
 Contact Resistance:50 Milliohms Max.
 Insulation Resistance:50 Megaohms Min.
 Operating Temperature:-55°C~+85°C
 Mating Force:3.0kg Max.
 Unmate Force:1.02kg Min.
 Durability:5000 Cycles Min.
 Terminal:Phosphor Bronze
 Gold Flash On Contact Area,
 Tin Plated On Solder Tails,Over Nickel
 Insulator:LCP(UL94V-0),Black
 Shell:Stainless Steel,Matte Tin Plated
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.30 X.* ±3* .X ±0.25 .X* ±2* .XX ±0.20 .XX* ±1* .XXX ±0.05 .XXX* ±0.5*
21253		MEI		
		CHECKED BY HZF		
		DRAWING BY CYP		
SCALE	NONE	REV.	A0	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A0		NEW RELEASE	HZF	04/27/2021