



△ Recommended P.C.B. Layout(Bottom View)

△ SPECIFICATION

Rated Voltage And Current:1.5A At 250V AC Min.
 Dielectric Withstanding Voltage:
 750V AC RMS For 1 Minute(Rev. 1.1)
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min. At 500V DC
 Durability (Life Test):1500 Cycles
 RoHS Compliant

△ No.	Description	Q'ty	Material	Remark
①	Housing	1	PBT+G.F.	21273:White 21283:Black
②	Terminal	4	Phosphor Bronze	Gold Flash On Contact Area, Tin Plated On Solder Tails, Over Nickel
③	Shell	1	Brass	Nickel Plated
④	Rear Shell	1	SPCC	Nickel Plated
△ ⑤	Bottom Cover	1	PBT+G.F.	

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ X ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05
21283		MEI		
		CHECKED BY	HZF	
		DRAWING BY	CYP	
SCALE	NONE	REV.	A2	UNIT mm

△ A2	Modify Data	HZF	03/15/2018
△ A1	Modify Data	HZF	03/09/2018
△ A0	NEW RELEASE		
NO. REV.	REVISIONS	CHK	DATE