



△ SPECIFICATION

Current Rating:5 Amp  
 Dielectric Withstanding Voltage:1000V AC Per Minute  
 Insulation Resistance:1000 Megaohms Min. At 500V DC  
 Contact Resistance:30 Milliohms Max. 10 Sec.  
 Operation Temperature:-55°C~+105°C  
 Insulator:PBT+25%G.F.(UL94V-0),Black  
 Contact:Brass,Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel  
 Shell:SPCC,Nickel Plated  
 Grounding Bracket:SPCC,Tin Plated  
 Riveted Insert:Brass,Tin Plated  
 Jack Screws:SPCC,Nickel Plated  
 RoHS Compliant

Pin	A±0.20	B±0.25	C±0.38	D
9	16.33	24.99	30.80	11.08
15	24.66	33.32	39.10	19.39
25	38.38	47.04	53.00	33.24
37	54.84	63.50	69.32	49.86

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ .X ±0.38 .XX ±0.30 .XXX ±0.05 ANG ±1°
21797		MEI		
		CHECKED BY HZF		
		DRAWING BY CYP		
SCALE	NONE	REV.	A1	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A1		Modify Data	HZF	12/05/2019
△ A0		NEW RELEASE	SHIN	02/20/2007