

SPECIFICATION

Current Rating:3 Amp

Contact Resistance:20 Milliohms Max.

Insulation Resistance:1000 Megaohms Min.



△ Withstand Voltage:1000V AC/Minute

Operation Temperature:-40°C~+105°C

Contact:Brass,Gold Flash Over Nickel

Insulator:PA6T+30%G.F.(UL94V-0),Black

RoHS Compliant



Pin	A	B	Pin	A	B
02	2.54	5.08	22	53.34	55.88
03	5.08	7.62	23	55.88	58.42
04	7.62	10.16	24	58.42	60.96
05	10.16	12.70	25	60.96	63.50
06	12.70	15.24	26	63.50	66.04
07	15.24	17.78	27	66.04	68.58
08	17.78	20.32	28	68.58	71.12
09	20.32	22.86	29	71.12	73.66
10	22.86	25.40	30	73.66	76.20
11	25.40	27.94	31	76.20	78.74
12	27.94	30.48	32	78.74	81.28
13	30.48	33.02	33	81.28	83.82
14	33.02	35.56	34	83.82	86.36
15	35.56	38.10	35	86.36	88.90
16	38.10	40.64	36	88.90	91.44
17	40.64	43.18	37	91.44	93.98
18	43.18	45.72	38	93.98	96.52
19	45.72	48.26	38	96.52	99.06
20	48.26	50.80	40	99.06	101.60
21	50.80	53.34		--	

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

21887

SCALE

NONE

APPROVED BY

Jason Wu

CHECKED BY

Leo Han

DRAWING BY

Michelle Lee

REV.

A1

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ±0.30

.XX ±0.20

ANG.

UNIT
mm



⚠	A1	Modify Data	HZF	10/24/2022
⚠	A0	NEW RELEASE	HZF	06/15/2018
NO.REV.	REVISIONS		CHK	DATE