



△ Recommended P.C.B. Layout

SPECIFICATION
 Current Rating:1A Max.
 Withstand Voltage:100V AC For One Minute
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:100 Megaohms Min.
 Temperature Range:-30°C~+80°C
 Insulator:LCP+30%G.F.(UL94V-0),Black
 △△ Contact:C5191
 Gold Flash Over All,Over Nickel
 △ Shell:SUS201,Matte Tin Plated Over Nickel
 Total Mating Force:3.57 kgf Max.
 Total Unmating Force:1.0 kgf Min.
 △ Durability:10000 Cycles Min.
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △
21919		MEI		
		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		.X ±0.30 X* ±3* .XX ±0.20 .X* ±2* .XXX ±0.10 .XX* ±1*
REV.	A3	UNIT	mm	△

NO.	REV.	REVISIONS	CHK	DATE
△	A3	Modify Data	HZF	11/14/2019
△	A2	Modify Data	HZF	11/07/2019
△	A1	Modify Data	HZF	12/02/2018
△	A0	NEW RELEASE	HZF	10/11/2017