



Recommended P.C.B. Layout

SPECIFICATION
 Current Rating:1A
 Withstanding Voltage:500V AC At Sea Level
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Mating Force:3.5 Kg Max.
 Unmating Force:1 Kg Min.
 Operation Temperature:-55°C~+85°C
 RoHS Compliant

Contact Finish	Item No.
Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel	22019
Gold Plated 30u" On Contact Area,Tin Plated On Solder Tails,Over Nickel	11083

No.	Description	Material	Remark	Q'ty
③	Housing	PBT	Black	1
②	Terminal	C5191H		4
①	Shell	Brass	Nickel Plated	1

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ X: ±2.0° .X ±0.2 .X' ±1.0° .XX ±0.1 .XX' ±0.5°
22019		MEI		
		CHECKED BY HZF		
		DRAWING BY CYP		
SCALE	NONE	REV.	A1	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A1		Modify Data	HZF	12/15/2017
△ A0		NEW RELEASE	HZF	03/29/2015