



SPECIFICATION
 Current Rating:1A
 Withstanding Voltage:500V AC At Sea Level
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Mating Force:3.5 Kg Max.
 Unmating Force:1 Kg Min.
 Operation Temperature:-55°C~+85°C
 RoHS Compliant

Contact Finish	Insulator Color	Item No.
Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel	Black	22019
Gold Plated 30u" On Contact Area,Tin Plated On Solder Tails,Over Nickel	Black	11083
Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel	White	22026
Gold Plated 30u" On Contact Area,Tin Plated On Solder Tails,Over Nickel	White	22027

No.	Description	Material	Remark	Q'ty
③	Housing	PBT		1
②	Terminal	C5191H		4
①	Shell	Brass	Nickel Plated	1

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ X° ±2.0° .X ±0.2 .X° ±1.0° .XX ±0.1 .XX° ±0.5°
22027		MEI		
		HZF		
		DRAWING BY		
		CYP		
SCALE	NONE	REV.	A1	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△A1		Modify Data	HZF	12/15/2017
△A0		NEW RELEASE	HZF	03/29/2015