



△ SPECIFICATION

Rated Voltage And Current:1.5A At 250V AC Min.
 △ Dielectric Withstand Voltage:750V AC(RMS)
 For 1 Minute(Rev. 1.1)
 500V AC(RMS)
 For 1 Minute(Rev. 2.0)
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min. At 500V DC
 Durability(Life Test):1500 Cycles
 Insertion Force:35N Max.
 Extraction Force:10N Min.
 RoHS Compliant

No.	Name	Material	Finish	Q'ty
1	Housing	PBT+G.F.	Black	1
2	Pin Term.	Phosphor Bronze	Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel(Rev. 1.1)	4
3	Shell	Brass	Nickel Plated	1

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05
22823		EMILY		
		CHECKED BY		
		HZF		
		DRAWING BY		
		GAO		
SCALE	NONE	REV.	A3	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△3	A3	Modify Data	HZF	02/10/2025
△2	A2	Modify Data	HZF	06/19/2012
△1	A1	Modify Data	EMILY	02/12/2009
△0	A0	NEW RELEASE	BECKY	10/25/2005

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.