





SPECIFICATIONS

- 1.Body : Brass,QQ-B-626
Gold Plated 3 Micro-Inches Min Thick Over Nickel
Plated 70Micro-Inches Min. Over Copper Strike
- 2.Insulator:Teflon MIL-P-19468,White
- 3.Contact Pin : Brass,QQ-B-626
Gold Plated 30 Micro-Inches Min Over Nickel
Plated 70Micro-Inches Min. Thick Over Copper Strike
- 4.Washer : Brass,QQ-B-613
Gold Plated 3 Micro-Inches Min Over Nickel
Plated 70Micro-Inches Min. Over Copper Strike
- 5.Nut : Brass,QQ-B-626
Gold Plated 30 Micro-Inches Min Over Nickel
Plated 70Micro-Inches Min. Thick Over Copper Strike



Recommended
Mounting Hole

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X .XX ±0.20 ANG. ±5°
10801		MEI		
		CHECKED BY		
		BECKY		UNIT mm
		DRAWING BY		
		HZF		
SCALE	NONE	REV.	A0	

NO.	REV.	REVISIONS	MEI	DATE
△A0	A0	NEW RELEASE	MEI	
			CHK	