




**SPECIFICATION**  
 Current Rating:1A AC/DC  
 Voltage Rating:125V AC Max.  
 Dielectric Withstanding Voltage:250V AC/Minute  
 Insulation Resistance:100 Megaohms Min.  
 Contact Resistance:20 Milliohms Max.  
 Operation Temp:-20°C~+85°C  
 Material:PA66(UL94V-0)  
 RoHS Compliant



Contacts	A	B
2	1.25	4.25
3	2.50	5.50
4	3.75	6.75
5	5.00	8.00
6	6.25	9.25
7	7.50	10.50
8	8.75	11.75
9	10.00	13.00
10	11.25	14.25
11	12.50	15.50
12	13.75	16.75
13	15.00	18.00
14	16.25	19.25
15	17.50	20.50

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.

01185

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE


.X ±0.25

.XX ±0.15

SCALE NONE

REV. B1

UNIT mm



NO.	REV.	REVISIONS	CHK	DATE
△	B1	Modify Data	HZF	07/08/2015
△	B0	NEW RELEASE	HZF	12/10/2009