




SPECIFICATION
 Current Rating:1A AC/DC
 Voltage Rating:125V AC Max.
 Dielectric Withstanding Voltage:250V AC/Minute
 Insulation Resistance:100 Megaohms Min.
 Contact Resistance:20 Milliohms Max.
 Operation Temp:-20°C~+85°C
 Material:PA66(UL94V-0)
 RoHS Compliant



Contacts	A	B
2	1.25	4.25
3	2.50	5.50
4	3.75	6.75
5	5.00	8.00
6	6.25	9.25
7	7.50	10.50
8	8.75	11.75
9	10.00	13.00
10	11.25	14.25
11	12.50	15.50
12	13.75	16.75
13	15.00	18.00
14	16.25	19.25
15	17.50	20.50

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.25 .XX ±0.15
01192		MEI		
		CHECKED BY	HZF	
SCALE	NONE	DRAWING BY	CYP	UNIT
		REV.	B1	mm

NO.	REV.	REVISIONS	CHK	DATE
△	B1	Modify Data	HZF	07/08/2015
△	B0	NEW RELEASE	HZF	12/10/2009