





Recommended P.C.B. Layout


△△ SPECIFICATION
 Current Rating: 3A AC/DC
 Voltage Rating: 250V AC Max.
 Withstanding Voltage: 1000V AC/Minute
 Operation Temperature: -25°C~+85°C
 Contact Resistance: 10 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Contact: Brass, Tin Plated Over Nickel
 Insulator: PA66(UL94V-0), Natural
 RoHS Compliant



△ 3~20 Pin



△ 2 Pin



△

Pin	A	B
2	2.50	7.50
3	5.00	10.00
4	7.50	12.50
5	10.00	15.00
6	12.50	17.50
7	15.00	20.00
8	17.50	22.50
9	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50
13	30.00	35.00
14	32.50	37.50
15	35.00	40.00
16	37.50	42.50
20	47.50	52.50

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY MEI		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.35 △ .XX ±0.25 △	△ A4	Modify Data	HZF	09/03/2019
01638		CHECKED BY HZF			△ A3	Modify Data	HZF	09/18/2018
SCALE NONE		DRAWING BY CYP			△ A2	Modify Data	HZF	03/24/2010
REV.	A4	UNIT mm	⊕	△ A1	Modify Data	BECKY	2004/11/19	A
				△ A0	NEW RELEASE			
				NO. REV.	REVISIONS	CHK	DATE	