



△△ SPECIFICATION


△ Current Rating: 1 Amps
 Withstanding Voltage: 1000V (1 Minute)
 Contact Resistance: 20 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min. At 500V DC
 Operating Temperature: -50°C ~ +105°C
 Shell: SPCC, Front: Nickel Plated, Rear: Tin Plated
 Insulator: PBT+30%G.F. (UL94V-0), White
 Contact: Brass, Gold Flash On Contact Area,
 Tin Plated On Solder Tails, Over Nickel
 RoHS Compliant




△




△



△△ 15 Pin



△△ 26, 44, 62 Pin



△

Pin	A	B	C	D	E	F
15	16.33	24.99	30.81	19.20	2.29	0.25
26	24.80	33.32	39.20	27.60	2.29	0.50
44	38.38	47.04	53.04	41.00	2.29	0.50
62	54.84	63.50	69.40	57.30	2.41	0.60

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △.X ±0.38 .X' ±3' .XX ±0.25 .XX' ±1' .XXX ±0.05 .XXX' ±0.5'
02754		EMILY		
		HZF		
		DRAWING BY		UNIT mm
		HAO		
SCALE	NONE	REV.	A4	NO. REV.

NO.	REV.	REVISIONS	CHK	DATE
△	A4	Modify Data	HZF	04/29/2015
△	A3	Modify Data	HZF	10/25/2013
△	A2	Modify Data	HZF	05/10/2012
△	A1	Modify Data	HZF	07/09/2009
△	A0	NEW RELEASE	SHIN	10/12/2006