



**SPECIFICATION**

Current Rating: 1 Amps  
 Withstanding Voltage: 500V(One Minute)  
 Insulation Resistance: 1000 Megaohms Min. At DC 500V  
 Contact Resistance: 30 Milliohms Max.  
 Operating Temperature: -40°C~+85°C  
 Contact: Brass  
 Gold Plated On Contact Area,  
 Tin Plated On Solder Tails, Over Nickel  
 Insulator: PBT+30%G.F.(UL94V-0), Black  
 Shell: SPCC, Nickel Plated Front, Tin Plated Rear  
 RoHS Compliant

Pin	A	B	C	D
09	16.92	24.99	30.81	19.20
15	25.25	33.32	39.20	27.70
25	38.96	47.04	53.04	41.10
37	55.42	63.50	69.40	57.30
50	52.81	61.00	67.00	55.10

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .X* ±3* .XX ±0.25 .XX* ±1* .XXX ±0.05 .XXX* ±0.5*
03192		MEI		
		HZF		
		DRAWING BY		
		CYP		
SCALE	NONE	REV.	A0	UNIT mm

NO.	REV.	DESCRIPTION	CHK	DATE
△ A0		NEW RELEASE	HZF	12/07/2016
		REVISIONS		