



**△△ SPECIFICATION**  
 Current Rating: 2 Amp  
 Voltage Rating: 250V AC Max.  
 Contact Resistance: 20 Milliohms Max.  
 Insulation Resistance: 500 Megaohms Min.  
 At 1000V DC  
 Withstand Voltage: 1000V AC/Minute < 0.5 Amps  
 Operation Temperature: -40°C ~ +125°C  
 Housing: PC (UL94V-2)  
 Contact: Phosphor Bronze  
 Gold Flash Over Nickel  
 Available For 24 Or 26 AWG Wire  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No. △△		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .XX ±0.25 ANG.
04810		MEI		
		CHECKED BY	HZF	
		DRAWING BY	CYP	
SCALE	NONE	REV.	B3	UNIT
				mm

NO.	REV.	REVISIONS	CHK	DATE
△	B3	Modify Data	HZF	07/01/2019
△	B2	Modify Data	HZF	01/17/2015
△	B1	Modify Data	HZF	07/18/2012
△	B0	NEW RELEASE	HZF	04/23/2007