



**△△ SPECIFICATION**  
 Current Rating: 1.5A Max.  
 Voltage Rating: 150V AC Max.  
 Operating Temperature: -40°C ~ +85°C  
 Relative Humidity: 70% ± 10% RH  
 Insulation Resistance: 500 Megaohms Min. Initial  
 At 500V DC  
 Contact Resistance: 20 Milliohms Max. Initial  
 30 Milliohms Max. Final  
 Durability: 750 Cycles  
 Dielectric Withstanding Voltage:  
 1000V RMS. At 60Hz, 1 Minute Between  
 Adjacent Contacts  
 1500V RMS. At 60Hz, 1 Minute Between  
 Shield And Contacts  
 Insulator: PBT+G.F.(UL94V-0), Gray  
 Contacts: Phosphor Bronze  
 Gold Plated 6u" Over All, Over Nickel  
 Cavity Conforms To FCC Rules And Regulations  
 Part 68, Subpart F.  
 RoHS Compliant

△△ Recommended P.C.B. Layout (Top View)  
 (PCB Board Thickness: 1.6mm) Tolerance: ±0.05

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.25 .XX ±0.13 .XXX ±0.05	△ B4	Modify Data	HZF	02/22/2016
04873		MEI			△ B3	Modify Data	HZF	08/23/2012
		CHECKED BY			△ B2	Modify Data	HZF	09/28/2011
		HZF		△ B1	Modify Data	EMILY	11/19/2008	
		DRAWING BY		△ B0	NEW RELEASE	BECKY	05/31/2006	
		CYP		NO. REV.	REVISIONS	CHK	DATE	
SCALE	NONE	REV.	B4	UNIT	mm			