



△△ SPECIFICATION

- Current Rating: 1 Amp
- Voltage Rating: 30V RMS Max.
- Dielectric Withstanding Voltage: 500V AC Min. For 1 Minute
- Insulator Resistance: 500 Megaohms Min. At 500V DC
- Contact Resistance: 20 Milliohms Max.
- △ Operating Temperature: -45°C ~ +105°C
- △ Insulator: PA66, Black
- Contact: Brass, Gold Flash Over Nickel
- RoHS Compliant

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △△△		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		△ B3	Modify Data	HZF	12/11/2019
05734		MEI		.X ±0.38		△ B2	Modify Data	HZF	12/04/2019
		CHECKED BY		.XX ±0.25		△ B1	Modify Data	HZF	02/25/2013
		HZF		△.XXX ±0.15		△ B0	Modify Data	HZF	05/16/2010
DRAWING BY		CYP		ANG. ±2°		△ B0	NEW RELEASE	HZF	05/16/2010
SCALE	NONE	REV.	B3	UNIT	mm	NO. REV.	REVISIONS	CHK	DATE