



Section A-A



Section A-A



Section A-A

SPECIFICATION

Current Rating:1.0 Amp
 Voitage Rating:30V RMS Max.
 Dielectric Withstanding Voltage:500V AC Min. For 1 Minute
 Insulator Resistance:1000 Megaohms Min. At 500V DC
 Contact Resistance:30 Milliohms Max.
 Operating Temperature:-45°C~+105°C
 Insulator:PBT+15%G.F.(UL94V-0)

Item	Color
05740	Black
05744	Red
05741	Blue

Contact:Brass,Gold Flash Over Nickel
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. Δ		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X \pm 0.38 .XX \pm 0.25 ANG \pm 2°
05741		MEI		
		HZF		
SCALE		REV.		UNIT
NONE		B3		mm

NO.	REV.	REVISIONS	CHK	DATE
Δ	B3	Modify Data	HZF	12/09/2019
Δ	B2	Modify Data	HZF	02/08/2017
Δ	B1	Modify Data	HZF	11/10/2010
Δ	B0	Modify Data	HZF	06/22/2009
Δ	B0	NEW RELEASE	HZF	06/22/2009