

1.02

5.08

1.91

5.20

Recommended P.C.B. Layout

△

SPECIFICATION

Current Rating:3Amp

Insulation Resistance:1000 Megaohms Min.

Contact Resistance:20 Milliohms Max.

Dielectric Withstanding:600V AC/DC

Operation Temperature:-40°C~+105°C

△ Contact:Phosphor Bronze,Gold Flash Over Nickel

Insulator:PA6T(UL94V-0),Black

RoHS Compliant

△

Pin 1

2.17

7.10

2.540

Pin 0.48X0.25

2.54XNo. Of Contacts-2.54±0.25

△ A

△

2.50

7.50±0.25

4.15△

△	Pin	A	Pin	A
	02	5.08	22	56.38
	03	7.62	23	58.92
	04	10.66	24	61.46
	05	13.20	25	64.00
	06	15.74	26	66.54
	07	18.28	27	69.08
	08	20.82	28	71.62
	09	23.36	29	74.16
	10	25.90	30	76.70
	11	28.44	31	79.24
	12	30.98	32	81.78
	13	33.52	33	84.32
	14	36.06	34	86.86
	15	38.60	35	89.40
	16	41.14	36	91.94
	17	43.68	37	94.48
	18	46.22	38	97.02
	19	48.76	39	99.56
	20	51.30	40	102.10
	21	53.84		

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △

06715

SCALE

NONE

REV.

A3

APPROVED BY

CHECKED BY

DRAWING BY

UNIT

mm

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
X. ±0.50
.X ±0.35
.XX ±0.25
.XXX ±0.05

△ A3

△ A2

△ A1

△ A0

NO. REV.

REVISIONS

CHK

DATE

MEI

HZF

CYP

A3

04/25/2020

10/09/2014

12/22/2009

08/14/2006