




SPECIFICATION
 Current Rating:3A AC/DC
 Voltage Rating:250V AC/DC
 Temperature Range:-25°C~+85°C
 Insulation Resistance:1000 Megaohms Min.
 Withstand Voltage:1000V AC/Minute
 Material:PBT(UL94V-0),Black
 RoHS Compliant



Pin	A	B	Pin	A	B
2	2.54	5.08	15	35.54	38.10
3	5.08	7.62	16	38.10	40.64
4	7.62	10.16	17	40.64	43.18
5	10.16	12.70	18	43.18	45.72
6	12.70	15.24	19	45.72	48.26
7	15.24	17.78	20	48.26	50.80
8	17.78	20.32	21	50.80	53.34
9	20.32	22.86	22	53.34	55.88
10	22.86	25.40	23	55.88	58.42
11	25.40	27.94	24	58.42	60.96
12	27.94	30.48	25	60.96	63.50
13	30.48	33.02	30	73.75	76.34
14	33.02	35.54	40	99.3	101.9

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 07139
 APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY CYP
 SCALE NONE REV. A2
 UNIT mm
 UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:
 X ±0.5
 .X ±0.25
 .XX ±0.2
 .XXX ±0.08

NO.	REV.	REVISIONS	CHK	DATE
A2		Modify Data	HZF	07/08/2015
A1		Modify Data	HZF	06/11/2010
A0		NEW RELEASE	HZF	11/05/2007