



△ SPECIFICATION

Insulator: PA66(UL94V-2), Nature
 Conductor: Copper Alloy, Nickel Plated
 Screw: Steel, Zinc Plated
 Temperature: -20°C ~ +150°C (VDE)
 Connecting Capacity: 4mm, (Cu, AWG)
 RoHS Compliant

Pin	L	Pin	L
01	6.5	07	66.0
02	16.4	08	76.0
03	26.3	09	86.0
04	36.2	10	96.0
05	46.1	11	106.0
06	56.0	12	116

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. **09861**
 SCALE NONE

APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY YBL
 REV. A4

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 Insulator: ±0.5
 Metal: ±0.2
 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△A4	A4	Modify Data	HZF	01/10/2022
△A3	A3	Modify Data	HZF	08/10/2020
△A2	A2	Modify Data	HZF	12/18/2013
△A1	A1	Modify Data	HZF	05/18/2013
△A0	A0	NEW RELEASE	HZF	12/26/2011