



**△△ SPECIFICATION**  
 Dielectric Withstanding Voltage:1000V AC Per Minute  
 Contact Resistance:10 Milliohms Max.  
 Insulation Resistance:5000 Megaohms Min.  
 Operation Temperature:-55°C~+125°C  
 Insulator:PBT+30%G.F.(UL94V-0),White  
 △ Contact:Brass,Gold Flash Over Nickel  
 Metal Shell:Steel,Tin Plated Over Nickel  
 RoHS Compliant

Pin	A±0.25	B±0.13	C±0.38	D±0.25	E±0.25
09	16.33	24.99	30.81	19.28	11.08
15	24.66	33.32	39.14	27.51	19.39
25	38.38	47.04	53.04	41.28	33.24
37	54.84	63.50	69.32	57.71	49.86

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.3 .XX ±0.3 .XXX ±0.3 ANG. ±2°
10584		EMILY		
		CHECKED BY HZF		
		DRAWING BY SAN		UNIT mm
SCALE	NONE	REV.	A4	

NO.	REV.	REVISIONS	CHK	DATE
△	A4	Modify Spec.	HZF	05/29/2014
△	A3	Modify P/N Code	HZF	01/21/2011
△	A2	Modify Data	HZF	12/18/2009
△	A1	Modify Dim.:7.9-->7.2&Add Spec.	BECKY	2004/11/04
△	A0	NEW RELEASE		