



△ SPECIFICATION

Current Rating: 16 Amps/Way Max.
 Voltage Rating: 300V AC
 Contact Resistance: 20 Milliohms Max.
 Withstanding Voltage: 2500V AC (1 Minute)
 Test Time = 60 Sec/1 PCS
 Wire Range: 12~26 AWG
 Operation Temperature: -40°C ~ +105°C
 Soldering Reliability: Test Temperature = 250°C ± 10°C / 5 Seconds Max.
 Torque: 5.0 Kgf.cm/M3
 Contact (Metal Housing): Copper Alloy, Nickel Plated
 Wire Guard: Copper Alloy, Tin Plated
 Terminal Screw: Steel, Galvanized With Cr3+ Plated
 Insulator Body (Housing): Polyamide (UL94V-0), Green
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 11573
 APPROVED BY EMILY
 CHECKED BY HZF
 DRAWING BY CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 ANG. ±1°

SCALE NONE REV. A1 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A1		Modify Data	HZF	10/31/2014
△ A0		NEW RELEASE	HZF	09/26/2009