



**△ SPECIFICATION**

Current Rating:16 Amp/Way Max.  
 Voltage Rating:300V AC  
 Contact Resistance:20 Milliohms Max.  
 Withstanding Voltage:2500V AC(1 Minute)  
 Test Time=60 Sec/1 PCS  
 Wire Range:12~26 AWG  
 Operating Temperature:-40°C~+105°C  
 Torque:5.0 Kgf.cm/M3  
 Soldering Reliability:  
 Test Temperature=250°C±10°C,5s Max.  
 Terminal Screw:Steel,Galvanized With Cr3+ Plated  
 Contact(Metal Housing):Copper Alloy,Nickel Plated  
 Wire Guard:Copper Alloy,Tin Plated  
 Insulator Body(Housing):Polyamide,UL94V-0,Green  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.30 .X ±0.15 .XX ±0.05 ANG. ±1°
13955		MEI		
		CHECKED BY HZF		
		DRAWING BY GAO		
SCALE	NONE	REV.	A1	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A1		Modify Spec.	HZF	03/12/2013
△ A0		NEW RELEASE	HZF	03/11/2010