



△ SPECIFICATION

Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec/1 PCS
 Wire Range:12~26 AWG
 Operating Temperature:-40°C~+105°C
 Torque:5.0 Kgf.cm/M3
 Soldering Reliability:
 Test Temperature=250°C±10°C,5s Max.
 Terminal Screw:Steel,Galvanized With Cr3+ Plated
 Contact(Metal Housing):Copper Alloy,Nickel Plated
 Wire Guard:Copper Alloy,Tin Plated
 Insulator Body(Housing):Polyamide,UL94V-0,Green
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.30 .X ±0.15 .XX ±0.05 ANG. ±1°
13956		MEI		
		CHECKED BY HZF		
		DRAWING BY GAO		
SCALE	NONE	REV.	A1	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A1		Modify Spec.	HZF	03/12/2013
△ A0		NEW RELEASE	HZF	03/11/2010