







Recommended P.C.B. Layout



Section A-A



Mating Draw (Ref)

SPECIFICATION

1.General Characteristics:

0.8mm Board To Board Male XXP SMT 180°
With Post Stacking Height=6.0mm

2.Material&Finish:

Insulator:PA46(UL94V-0),Beige
Conact:Phosphor Bronze,Gold Plated

3.Electrical Characteristics:

Current Rating:0.5Amp AC/DC
Voltage Rating:100V AC/DC
Insulation Resistance:100 Megaohms Min.
Withstanding Voltage:500V(RMS) For One Minute
Contact Resistance:40 Milliohms Max.

4.Environmental Characteristics:

Operation Temperature Range:-40°C~+105°C

5.RoHS Compliant

Male Series No.	Female Series No.	A1	H
1634	1636	3.55	6.00

Pin	A	B	C	D	Pin	A	B	C	D
10	6.20	4.90	5.00	3.20	34	15.80	14.50	14.60	12.80
12	7.00	5.70	5.80	4.00	36	16.60	15.30	15.40	13.60
14	7.80	6.50	6.60	4.80	38	17.40	16.10	16.20	14.40
16	8.60	7.30	7.40	5.60	40	18.20	16.90	17.00	15.20
18	9.40	8.10	8.20	6.40	50	22.20	20.90	21.00	19.20
20	10.20	8.90	9.00	7.20	60	26.20	24.90	25.00	23.20
22	11.00	9.70	9.80	8.00	68	29.40	28.10	28.20	26.40
24	11.80	10.50	10.60	8.80	70	30.20	28.90	29.00	27.20
26	12.60	11.30	11.40	9.60	80	34.20	32.90	33.00	31.20
28	13.40	12.10	12.20	10.40	90	38.20	36.90	37.00	35.20
30	14.20	12.90	13.00	11.20	100	42.20	40.90	41.00	39.20
32	15.00	13.70	13.80	12.00					

DRAWING No.

14434

APPROVED BY

MEI

CHECKED BY


HZF

DRAWING BY

SONG

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
.X ±0.20
.XX ±0.15
ANG.

UNIT
mm



SCALE

NONE

REV.

A2

NO. REV.

REVISIONS

CHK

DATE

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.