




△ Recommended P.C.B. Layout



△



△ Section B-B



△ Section A-A

△ SPECIFICATION

Current Rating:1A
 Dielectric Withstanding Voltage:1000V RMS/Minute
 Insulator Resistance:5000 Megaohms Min.
 Operating Temperature:-55°C To 85°C
 Contact Resistance:20 Milliohms initial.
 30 Milliohms After Test.
 Contact:Phosphor Bronze,Tin Plated Over Nickel
 Insulator:PBT(UL94V-0)
 RoHS Compliant

Pin	A	B
40	35.56	33.78
42	37.34	35.56
48	42.67	40.89
52	46.23	44.45
54	48.01	46.23
56	49.78	48.01
58	51.56	49.78
60	53.34	51.56
62	55.12	53.34
64	56.90	55.12

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.


DRAWING No.
 17883

APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY CYP

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 ANG.

SCALE NONE

REV. A2



NO.	REV.	REVISIONS	CHK	DATE
△ A2		Modify Data	HZF	02/07/2017
△ A1		Modify Data	SHIN	08/31/2006
△ A0		NEW RELEASE	BECKY	07/19/2004