



△ SPECIFICATION
 Current Rating: 1 Amp
 Dielectric Withstanding Voltage: AC 1000V For 1 Minute
 Insulation Resistance: 1000 Megaohms Min. At DC 500V
 Contact Resistance: 30 Milliohms Max. At DC 100mA
 Operation Temperature: $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$
 Housing: LCP, Nature
 Contact: Brass,
 Gold Plated 10u" On Contact Area
 Tin Plated On Solder Tails, Over Nickel
 RoHS Compliant

Pin	A	B	C
24	11.95	10.0	0.0
48	23.95	22.0	12.0
72	35.95	34.0	24.0
96	47.95	46.0	36.0
120	59.95	58.0	48.0
144	71.95	70.0	60.0
168	83.95	82.0	72.0
192	95.95	94.0	84.0

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 18217		APPROVED BY EMILY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
		CHECKED BY HZF		X. ± 0.5	
		DRAWING BY YBL		.X ± 0.25	
SCALE NONE		REV. A2		.XX ± 0.15	
				UNIT mm	

NO.	REV.	REVISIONS	CHK	DATE
△ A2		Modify Data	HZF	02/16/2022
△ A1		Modify Data	HZF	12/20/2013
△ A0		NEW RELEASE	HZF	01/02/2009