



SPECIFICATION
 Current Rating:1.5A/Contact Terminal
 Voltage Rating:30V DC
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Withstanding Voltage:500V AC At Sea Level
 Mate Force:3.75Kgf Max.
 Unmate Forec:1.02Kgf Min.
 Terminal Retenion:1.2Kgf Min.
 RoHS Compliant

| ④ | Back Shell | 1 | SPCC | Nickel Plated |
|-----|-------------|------|-----------|---|
| ③ | Front Shell | 1 | SPCC | Nickel Plated |
| ② | Contact | 4 | C2680 | Gold Flash On Contact Area, Tin Plated On Solder Tails, Over Nickel |
| ① | Housing | 1 | PBT,White | — |
| No. | Description | Q'ty | Material | Remark |

4U CON 元化興業股份有限公司
 4U CON TECHNOLOGY INC.

| | | | | |
|-------------|------|-------------|----|---|
| DRAWING No. | | APPROVED BY | | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.35 X.* ±5.0° .X ±0.25 .X* ±4.0° .XX ±0.20 .XX* ±3.0° .XXX ±0.15 .XXX* ±2.0° |
| 18608 | | MEI | | |
| | | HZF | | |
| | | DRAWING BY | | UNIT mm |
| | | CYP | | |
| SCALE | NONE | REV. | A1 | |

| | | | | |
|-----|------|-------------|-----|------------|
| NO. | REV. | REVISIONS | CHK | DATE |
| ① | A1 | Modify Data | HZF | 07/12/2017 |
| ② | A0 | NEW RELEASE | HZF | 01/03/2017 |