







Recommended P.C.B. Layout

△ SPECIFICATION

Current Rating: 10A/Way Max.
 Voltage Rating: 150V AC
 Withstanding Voltage: 2000V AC/Minute
 Contact Resistance: 20 Milliohms Max.
 Wire Range: 16~30 AWG
 Torque: 2.0kgf.cm/M2
 Operating Temperature: -40°C~+105°C
 Terminal: Copper Alloy, Tin Plated
 Screw: Steel, Galvanized And With Cr3+ Plated
 Wire Guard: Stainless Steel
 Insulator: Polyamide(UL94V-0), Blue
 RoHS Compliant



4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

19963

SCALE

NONE

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY


WSS

REV.

B1

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 X. ± 0.50
 .X ± 0.30
 .XX ± 0.20
 ANG. $\pm 1^\circ$

UNIT
 mm



⚠	B1	Modify Data	HZF	03/05/2025
⚠	B0	NEW RELEASE	HZF	10/26/2014
NO.REV.	REVISIONS		CHK	DATE