







Recommended P.C.B. Layout

△ SPECIFICATION

Current Rating: 10A/Way Max.
 Voltage Rating: 150V AC
 Withstanding Voltage: 2000V AC/Minute
 Contact Resistance: 20 Milliohms Max.
 Wire Range: 16~30 AWG
 Torque: 2.0kgf.cm/M2
 Operating Temperature: -40°C~+105°C
 Terminal: Copper Alloy, Tin Plated
 Screw: Steel, Galvanized And With Cr3+ Plated
 Wire Guard: Stainless Steel
 Insulator: Polyamide(UL94V-0), Blue
 RoHS Compliant



4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

20193

APPROVED BY
 EMILY

CHECKED BY
 HZF

DRAWING BY
 WSS

SCALE


NONE

REV.

B1

UNLESS OTHERWISE
 SPECIFIED
 TOLERANCES ARE
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 ANG. ±1°

UNIT
 mm



△ B1

Modify Data

HZF

03/05/2025

△ B0

NEW RELEASE

HZF

10/26/2014

NO. REV.

REVISIONS

CHK

DATE