






Length(L)	Tolerances
0~30	±0.30
30~60	±0.40
60~120	±0.50
120~220	±0.60



1 SPECIFICATION

Voltage Rating:300V AC
Current Rating:12A/Way Max.
Contact Resistance:20 Milliohms Max.
Withstanding Voltage:1600V AC/Minute
Wire Range:16~24 AWG
Torque:2.5 Kgf.cm/M2
Operation Temperature:−40°C~+105°C
Contact:Copper Alloy,Nickel Plated
Terminal Screw:Steel,Galvanized With Cr3+ Plated
Wire Guard:Copper Alloy,Tin Plated
Insulator Body:Polyamide(UL94V-0),Gray
RoHS Compliant

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

20321

SCALE

NONE

APPROVED BY

Jason Wu

CHECKED BY

Leo Han

DRAWING BY

Michelle Lee

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

X. ± 0.50

 $\bar{X} \pm 0.40$ $\pm 0.30 \triangle 1$

ANG. $\pm 1^\circ$

UNIT	mm
------	----



⚠	B1	Modify Data	HZF	03/27/2026
⚠	B0	NEW RELEASE	HZF	10/04/2018
NO.REV.	REVISIONS		CHK	DATE