

△△ SPECIFICATION

Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec./1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature=250°C±10°C/
 5 Seconds Max.
 Wire Range:12~26 AWG
 Torque:5.0 Kgf.cm/M3
 Insulator Body(Housing):Polyamide(UL94V-0),Black
 Contact(Metal Housing):Copper Alloy,Nickel Plated
 Wire Guard:Copper Alloy,Tin Plated
 Screw:Steel,Galvanized With Cr3+ Plated
 RoHS Compliant



4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.

20550

APPROVED BY

MEI

CHECKED BY


HZF

DRAWING BY

YBL

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X. ±0.50
 .X ±0.30
 .XX ±0.20
 ANG. ±1°

UNIT mm



NO.	REV.	REVISIONS	CHK	DATE
△ A4		Modify P/N Code	HZF	08/07/2014
△ A3		Modify Spec.	HZF	02/12/2014
△ A2		Modify Data	HZF	12/16/2011
△ A1		Modify Data	HZF	06/29/2010
△ A0		NEW RELEASE	HZF	04/10/2009

SCALE

NONE

REV.

A4

NO. REV.

REVISIONS

CHK

DATE