



SPECIFICATION
 Withstand Voltage:300V DC,10S
 Contact Resistance:1.0 Ohms Max.
 Insulation Resistance:5 Megaohms Min.
 The Cable Assembly Must 100% Test
 RoHS Compliant

Pin Assignment	
P1	P2
1	1
2	2
3	3
—	—
59	59
60	60

No.	Name	Q'ty	Description
①	Wire	---	UL2678,PH0.635mm 60P Flat Cable 30 AWG(7/0.102TC) PVC Gray Marking Red Side
②	Conn. 2 Set		P/N:20837,1.27X1.27 IDC Socket For Flat Cable 0.635mm 60P Without SR With Bump Contact:Phosphor Bronze Selective Gold Flash Over Nickel Insulator:PBT+30%G.F.(UL94V-0),Black

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.40 .XX ±0.25 .XXX ±0.15 ANG. ±3°
20843		MEI		
		CHECKED BY		
		HZF		
		DRAWING BY		
		CYP		
SCALE	NONE	REV.	A0	UNIT mm

△ A0	NEW RELEASE	HZF	05/11/2016
NO.REV.	REVISIONS	CHK	DATE